

Warm air heaters / HT2000 OUH heater range Oil fired suspended heaters

High efficiency

CE & Building Regulations Compliant

Optional sealed combustion circuit

Heat exchanger made of T430 stainless steel

Automatic operation

Optimised control

Centrifugal options available

Space saving off floor installation



“Taylor” made solutions from the company with the know - how



Axial fan heaters

For conventional cross flow warm air discharge.



Centrifugal fan heaters

For ducted heating systems.

Warm air heating / HT2000 - OUH heaters Product range information

These high efficiency, fuel efficient suspended heaters comply with current CE and building regulations. With automatic ignition, room sealed combustion and optimised control they are ideal space saving heaters.

Visit us online: www.harrytaylor.co.uk

Warm air heaters / HT2000 OUH heater range

Oil fired suspended heaters

Compact, quiet & highly efficient HT2000 OUH oil fired unit heaters provide cost effective heating for many commercial & industrial buildings. Offering space saving 'off-floor' mounting OUHA oil unit heaters discharge warmth directly into the space to be heated in a conventional cross-flow manner. OUHC versions are suitable for ducted systems.

Model				75	100	150	200	
Output (nominal)		High Fire (Max)		kW	20	30	45	60
		Low Fire (Min)		kW	16	24	34	45
Airflow	Volume	OUH F	m3/s	0.7	0.82	1.19	1.94	
		OUH C	m3/s	1.0	0.82	1.19	1.88	
	Throw	OUH F	m	8.5	16	25	34	
	Fan static	OUH C	Pa	275	305	275	384	
Electrics	Supply	Standard	V/ph/Hz	230/1/50				
	Run current	OUH F	amp	0.94	0.46	0.48	1.7	
		OUH C	amp	4.3	4.33	5.54	8.0	
Fuel Oil	Connection		BSP/Rc	1/4				
	Consumption		l/h	2.18	3.18	5.32	6.70	
Mounting Height	OUH F	Min	m	2.50		3.00		
		Max	m	3.00		5.00		
Overall Dimensions	Height		mm	806	1043	1049	1049	
	Width		mm	555	780	780	780	
	Depth	OUH F	mm	868	1106	1115	1150	
		OUH C	mm	1163	1470	1469	1469	
Installation Clearances		Top	mm	1000				
		Side	mm	500				
			mm	400				
Flue diameter			mm Ø		400			
Combustion Air Spigot			mm Ø	400				
Maximum Combustion Duct Length			m	120	100	81	21	
Noise Level - OUH F models			dB(A)	46	54	52	53	
Nett Weight		OUH F	kg	53	126	126	126	
		OUH C	kg	91.5	142	142	142	

Harry Taylor Southern office:
Kitsons works, Aylesbury Road,
Bromley, Kent, BR2 0QZ, UK

Southern office tel: 020 8464 0915
southernoffice@harrytaylor.co.uk

Harry Taylor Northern office:
Guide Bridge Mill, South street,
Bromley, Kent, BR2 0QZ, UK

Northern office: 0161 308 4550
northernoffice@harrytaylor.co.uk

 **Harry Taylor**
www.harrytaylor.co.uk